Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 194562

Microsemi LAWRENCE

TECHNICAL DATA

PNP POWER TRANSISTOR SILICON AMPLIFIER

Qualified per MIL-PRF-19500/582

Devices		*Qualified Level*
2N5679	**2N5680**	**JAN JANTX JANTXV**

MAXIMUM RATINGS (T_A = 25^{0}C unless otherwise noted)

Ratings	Symbol	2N5679	2N5680	Unit
Collector-Emitter Voltage	V_{CEO}	100	120	Vdc
Collector-Base Voltage	V_{CBO}	100	120	Vdc
Emitter-Base Voltage	V_{EBO}	4.0	4.0	Vdc
Collector Current	I_C	1.0	1.0	Adc
Base Current	I_B	0.5	0.5	Adc
Total Power Dissipation @ T_A = +25^{0}C(1) @ T_C = +25^{0}C(2)	P_T	1.0 10	1.0 10	W W
Operating & Storage Temperature Range	T_{op}, T_{stg}	-65 to +200	-65 to +200	°C

THERMAL CHARACTERISTICS

Characteristics	Symbol	Max.	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	17.5	^{0}C

1) Derate linearly 5.7 mW/^{0}C for T_A > +25^{0}C
2) Derate linearly 57 mW/^{0}C for T_C > +25^{0}C



TO-39*
(TO-205AD)

*See appendix A for package outline

ELECTRICAL CHARACTERISTICS (T_A = 25^{0}C unless otherwise noted)

Characteristics	Symbol	Min.	Max.	Unit
OFF CHARACTERISTICS				
Collector-Emitter Breakdown Voltage I_C = 10 mAdc 2N5679 2N5680	$V_{(BR)CEO}$	100 120		Vdc
Emitter-Base Cutoff Current V_{EB} = 4.0 Vdc	I_{EBO}		1.0	µAdc
Collector-Emitter Cutoff Current V_{CE} = 70 Vdc 2N5679 V_{CE} = 80 Vdc 2N5680	I_{CEO}		10	µAdc
Collector-Emitter Cutoff Current V_{BE} = 1.5 Vdc V_{CE} = 100 Vdc 2N5679 V_{CE} = 120 Vdc 2N5680	I_{CEX}		100	nAdc

ELECTRICAL CHARACTERISTICS (con't)

Characteristics	Symbol	Min.	Max.	Unit
ON CHARACTERISTICS				
Forward Current Transfer Ratio I_C = 250 mAdc, V_{CE} = 2.0 Vdc I_C = 500 mAdc, V_{CE} = 2.0 Vdc I_C = 1.0 Adc, V_{CE} = 2.0 Vdc	h_{FE}	40 20 5	150	
Collector-Emitter Saturation Voltage I_C = 250 mAdc, I_B = 25 mAdc I_C = 500 mAdc, I_B = 50 mAdc	$V_{CE(sat)}$		0.6 1.0	Vdc
Base-Emitter Saturation Voltage I_C = 250 mAdc, I_B = 25 mAdc I_C = 500 mAdc, I_B = 50 mAdc	$V_{BE(sat)}$		1.1 1.3	Vdc
DYNAMIC CHARACTERISTICS				
Magnitude of Common Emitter Small-Signal Short Circuit Forward-Current Transfer Ratio I_C = 0.1 Adc, V_{CE} = 10 Vdc, f = 10 kHz	$\lvert h_{fe} \rvert$	3.0		
Small Signal Short Circuit Forward-Current Transfer Ratio I_C = 0.2 Adc, V_{CE} = 1.5 Vdc, f = 1.0 kHz	h_{fe}	40		
Output Capacitance V_{CB} = 20 Vdc, I_E = 0, f = 1 MHz	C_{obo}		50	pF

SAFE OPERATING AREA

DC Tests

T_C = +25^{0}C, 1 Cycle, t ≥ 0.5 s

Test 1

V_{CE} = 2 Vdc, I_C = 1.0 Adc

Test 2

V_{CE} = 10 Vdc, I_C = 1.0 Adc

Test 3

V_{CE} = 90 Vdc, I_C = 50 mAdc